

# Fire Rating Information Sheet

## Architectural Fusions

	<b>Class A Fire Rated</b>	<b>UL 10B &amp; 10C (Standard for Fire Tests of Door Assemblies)</b>
<b>Belbien</b>	All Belbien Patterns, except MT  <i>UL- 723</i>	60 minute rating for application to wood covered composite or wood core type fire door surfaces as well as door frames  60 minute rating for W Series application to hollow metal and metal composite fire door surfaces as well as door frames  CY Series rated up to 3 hours for metal door surfaces and frames
<b>LG</b>	All LG Patterns, except NC and PW  <i>ASTM E-84</i>	45 minute rating for application to wood covered composite or wood core type fire door surfaces as well as door frames  90 minute rating for application to hollow metal and metal composite fire door surfaces as well as door frames
<b>Reatec</b>	All Reatec Patterns  <i>ASTM E-84</i>	45 minute rating for application to wood covered composite or wood core type fire door surfaces as well as door frames  90 minute rating for TA Series application to hollow metal and metal composite fire door surfaces as well as door frames  TC Wood Series rated up to 3 hours for metal door surfaces and frames
<b>Reatec on 1/8” Sintra Panel</b>	All Reatec Patterns  <i>ASTM E-84</i>	